



ELECTRICAL CHARACTERISTICS:
 R25C=10,000 OHMS NOM
 ±0.1 °C, 0C TO 100C (4PT. CALIBRATION)
 0.01 °C RESOLUTION
 <100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:
LEADS:
 #24 AWG BELDEN CABLE
 7/32 STRANDED, LENGTH=10' NOM
 HI FLEX, BLACK INSULATION JACKET
 QTI P/N: QT01002-238

BELDEN P/N: 1508A

HOUSING:
 316 STAINLESS STEEL
 7/16" HEX, XD 1/8-27 NPT, PROBE=1.0" X .187"
 QTI P/N: QT01005-291

NOTES:

| | INITIAL | DATE |
|------------|---------------------|--------------|
| DRAWN | BR | 11/03/09 |
| ENG APPR. | <i>Greg Kochaer</i> | 11 03, 2009 |
| MAT APPR. | <i>John Larson</i> | Nov 03, 2009 |
| Q.A. APPR. | <i>Dan & Mm</i> | Nov 03, 2009 |



2108 CENTURY WAY
 BOISE, ID 83709
 WWW.THERMISTOR.COM

QTI PART NUMBER: **DTU6001-002-C** REV **-**

SIZE **A** DWG. NO. **DTU6001-002-C.SLDDRW**

| | | |
|----------|----------|---------|
| 11/03/09 | - | BR |
| DATE | REVISION | INITIAL |

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.