



ELECTRICAL CHARACTERISTICS:
R25C=10,000 OHMS NOMINAL

MECHANICAL CHARACTERISTICS:

LEADS:
#24 AWG BELDEN CABLE
7/32 STRANDED, LENGTH=5' NOM
HI FLEX, BLACK JACKET
QTI P/N: QT01002-238

BELDEN P/N: 1508A

HOUSING:
NICKEL PLATED #6 RING LUG
QTI P/N: QT01005-231

NOTES:
HEATSHRINK OVER BARREL AND CABLE

	INITIAL	DATE
DRAWN	BR	6/16/09
ENG APPR.	<i>Jay Kochaver</i>	01 20, 2010
MAT APPR.	<i>John Larson</i>	Jan 20, 2010
Q.A. APPR.	<i>David & M...</i>	Jan 20, 2010



2108 CENTURY WAY
BOISE, ID 83709
WWW.THERMISTOR.COM

QTI PART NUMBER:

DTU6009-003

REV
B

SIZE DWG. NO.

A DTU6009-003.SLDDRW

SHEET 1 OF 1

1/19/10	B	BR
6/16/09	A	BR
05/04/09	-	BR
DATE	REVISION	INITIAL

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±1/8
.X ±0.1
.XX ±0.02
.XXX ±0.005

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.