



ELECTRICAL CHARACTERISTICS:
 R25C=10,000 OHMS NOM
 ±0.1 °C FROM 0C TO 100C (4PT. CALIBRATION)
 0.01 °C RESOLUTION
 <100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:
LEADS:
 #22AWG PVC CABLE, STRANDED
 GRAY JACKET
 QTI P/N: QT01002-292

HOUSING:
 POLYIMIDE KAPTON TUBE
 1" X .136"
 QTI P/N: QT01010-044

NOTES:
 HID VERSION
 CALIBRATED AT 0C, 25C, 70C, 100C

	INITIAL	DATE
DRAWN	BC	2/8/10
ENG APPR.	<i>Gay Kochavaev</i>	02 08, 2010
MAT APPR.	<i>John Lange</i>	Feb 08, 2010
Q.A. APPR.	<i>Daniel & Ann</i>	Feb 08, 2010

2108 CENTURY WAY
 BOISE, ID 83709
 WWW.THERMISTOR.COM

QTI PART NUMBER: DTU6020-001-C REV -

SIZE DWG. NO.
A DTU6020-001-C.SLDDRW

DATE	REVISION	INITIAL
2/8/10	-	BC

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005

SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.