



SPECIFICATIONS
RESISTANCE VALUE AND TOLERANCE: R@25C=100 OHMS +/- 1%
OTHER ELECTRICAL CHARACTERISTICS: NTC=-3.5%/C @ 25C
LEADS: #28 AWG (.013) SOLDER PLATED COPPER
HOUSING:
OTHER MECHANICAL SPECIFICATIONS: DIA=.095, EPOXY COATING
NOTES: DISSIPATION CONST=2mW/C MIN TIME CONSTANT=10 SEC. MAX

DRAWING FILE NAME: 6002229.DWG	
ORIGINATOR: <i>[Signature]</i>	DATE: 5/8/00
ENGINEER: <i>[Signature]</i>	DATE: 5/8/00
SALES MGR.: <i>[Signature]</i>	DATE: 5/8/00
QUALITY MGR.: <i>[Signature]</i>	DATE: 5/15/00
PROD. MGR.: <i>[Signature]</i>	DATE: 5/8/00

QUALITY THERMISTOR INC
 2108 CENTURY WAY
 BOISE, ID 83709
 PH: 208-377-3373
 FAX: 208-376-4754

DESCRIPTION: X, 100 OHM, 1% .	QTI PART NUMBER: QT06002-229	REV: -
TOLERANCES: X=0.1" XX=0.02" XXX=0.001"	JOB NUMBER:	PAGE 1/1

NO.	DATE	REVISION	APPROVAL
1	5-8-00	-	JH

THIS DRAWING AND THE INFORMATION IS THE PROPERTY OF QUALITY THERMISTOR AND ALL UNAUTHORIZED USE AND REPRODUCTION IS PROHIBITED