



UNCONTROLLED DRAWING

ELECTRICAL CHARACTERISTICS:
 R25C=10,000 OHMS +/-10%
 RT CURVE Z, NTC=-4.4%/C @ 25C
 POWER RATING: .125W @25C, DERATE TO 125C
 THERMAL TIME CONSTANT: 60 SEC. MAX
 DISSIPATION CONSTANT: 2.5mW/C MIN
 OPERATING TEMPERATURE: -55C TO 125C
 STORAGE TEMPERATURE: -55C TO 150C

MECHANICAL CHARACTERISTICS:
 LEADS:
 SN60/PB40 TINNED DUMET

NOTES:



Quality Thermistor, Inc. 2108 CENTURY WAY
 BOISE, ID 83709

QTI PART NUMBER: QTGN12-12	REV -
--------------------------------------	----------

SIZE A	DWG. NO. QTGN12-12
------------------	-----------------------

SCALE: 1:1	APPROVED FORM: QT05006-168 REV.-	SHEET 1 OF 1
------------	-------------------------------------	--------------

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005