


ATTENTION OEM'S
Introducing the NEW:
micro IRt/c

The World's Smallest and Lowest Cost IRt/c™



Features

- Small Size
- Lowest Cost
- Variety of mounting options
- Self powered
- Air purge (optional)

Specifications

	P/N	Model	2% Linear Temperature Range
Recommended Sensing Ranges	150041	μIRt/c-K-80F/27C	40-118° F (4-48° C)
	150042	μIRt/c-K-98.6F/37C	77-104° F (25-40° C)
	150040	μIRt/c-K-140F/70C	90-180° F (32-82° C)
	150043	μIRt/c-K-180F/90C	170-220° F (77-104° C)
	150044	μIRt/c-K-240F/120C	220-245° F (104-118° C)
	150045	μIRt/c-K-280F/140C	270-310° F (132-154° C)
	150046	μIRt/c-K-340F/170C	330-370° F (166-188° C)
	150047	μIRt/c-K-440F/220C	415-465° F (213-241° C)
Ambient Temperature Range	-40 to 212°F (-40 to 100 °C)		
Sensing Range - All Models	0 to 975°F (-18 to 524 °C) with linearization at readout		
Field of View	approximately 1:2 (100°)		
Minimum Spot size	3 mm (.1")		
Spectral Response	5.5 to 20 μm		
Output	K type thermocouple		
Impedance	15 – 40 Kohms, varies depending on temperature range		
Emissivity (e)	.90		
Resolution	Approximately 0.0003°C (Johnson Noise limited)		
Response Time	50 millisecond time constant (typical)		
Accuracy (Interchangeability)	1% to factory calibration conditions		
Dimensions	0.25" (6.3 mm) Dia. x 1.0" (25.4 mm)		
Housing	Stainless Steel		
Cable Assembly	3 feet of unshielded, duplex insulated, type K, 24 AWG, PFA jacket rated to 500 °F (260 °C) (Shielded cable available upon request)		
Humidity	Non-Condensing		
Power Requirements	None, self-powered signal output		
Sealed	Hermetically sealed, exceeds NEMA 4X, IP67		
Weight	Approximately 30 grams (1 oz.)		
Input Device Compatibility	It is recommended to use input devices with less than 1 nA of leakage current to minimize offsets, and sensor break detection should be set to 40 kohm maximum.		



micro IRt/c Accessories

APJ-1 Air Purge Jacket P/N 150066



This convenient and inexpensive kit makes it possible to use the micro IRt/c™ with air for service in harsh environments. Measuring only 3/8" x 3" (9.5 x 76 mm) overall, the APJ-1 is physically small enough to fit into tight areas and closely monitor process temperatures from the optimum position - up close. This air purge kit ensures that the performance of a micro IRt/c does not degrade because of contamination by deposits of airborne chemicals or particles on the sensor. Efficient in design, the APJ-1 requires as little as 3.5 SCFH (1.7 L/min) of air to protect a micro IRt/c. In addition to keeping a micro IRt/c clean, the airflow through the air purge jacket can cool a micro IRt/c, allowing it to operate in environments of up to 347 °F (175 °C) with only 35 SCFH (17 L/min) at 5 psig (0.33 bar).

Features

- Small Size - 3/8" dia. x 3" long (9.5 x 76 mm)
- Aluminum housing
- Attaches to standard 3/8" tube fitting or 3/8" ID tubing
- Air purge and cooling



150062 & 836068
micro Thru-Fitting & MB-2 Mounting Bracket
plastic fitting with lock nut, sealing nut, and hub
1.17" x 0.59" (29.7 x 14.99 mm)
PG-7 thread



150037
MB-5 micro clamp mounting bracket
Stainless Steel, with silicone cushions
0.25" diameter



150038
MB-4 APJ-1 clamp mounting bracket
Stainless Steel, with silicone cushions
0.38" diameter



150065
APJ-1 Omega clamp
metal clamp with rubber cushion for mounting
1.81" x 0.78" (45.97 x 19.81 mm)



108000
IRt/c connector kit
type K thermocouple connectors



150064
micro Omega clamp
metal clamp with rubber cushion for mounting
1.81" x 0.78" (45.97 x 19.81 mm)



150063
APJ-1 Thru-Fitting
plastic fitting with lock nut, sealing nut and hub
1.17" x 0.59" (29.7 x 14.99 mm)
PG-7 thread

YOUR LOCAL SALES REPRESENTATIVE IS:

***Increasing your production
throughput, at an affordable cost***

Visit www.exergen.com (Industrial Division) for up to date detailed specifications on all products, and articles on the ***SPEEDBOOST*** methods!!

EXERGEN Corporation • 51 Water Street • Watertown, MA 02472 • 617.923.9900 • (F) 617-923-9911 • www.exergen.com

WWW.REDFISHSENSORS.COM

877-253-5755

P/N 818563